

QRT-100 CLEAR TIMBER FIRE RETARDANT - SEALER:

Product Summary

- A specialized water based clear sealer coating
- Non-tonic, low VOC, environmentally friendly
- Developed for use as a sealer over the **final coat of the QRT-100 Timber Fire Retardant**
- May be used for interior and exterior applications
- QRT-100 Top Sealer is used over **QRT-100 Timber Fire Retardant** prior to application of subsequent top coats

Components

- Resin binder : Modified acrylic polymer
- Volume solids : 32% (clear)

Application of the QRT-100 Timber Fire Retardant Clear Sealer

- Stir well using a broad flat paddle in a scooping motion to use and occasionally during use
- Do not thin this product.
- Apply one (1) coat by brush, good quality roller or airless spray to achieve a recommended WFT (Wet Film Thickness) of 100 micron.
- Coverage approximately 10 m² per litre at 100 microns wet.
Coverage will vary depending on the profile and porosity of the surface
- As may be required recoat recommended in 4 – 5 hours at 25oC with good air ventilation
- In damp, cool or humid conditions, drying time will be extended
- Touch dry in 30 – 60 minutes
- Check weather forecasts and do not paint where forecasts indicate that rain is imminent, the temperature is likely to fall below 10oC or relative humidity to exceed 80%. Do not attempt to apply in extreme heat.

Other Information

- Clean up: Water
- Colour: Clear
- Shelf life: 12 months, provided correctly stored in a dry, sheltered location with storage temperature of 25oC, 6 months with storage temperature of 25oC – 40oC

Safety

Ensure good ventilation during application and drying. The product is non-flammable. Keep out of reach of children. Do not breathe vapour or spray. Do not smoke during application. Wear eye protection. Refer to product material safety data sheet for full information.

Disposal

When cleaning up after painting, ensure the paint does not get into gutters or drains as it may contaminate waterways. For a free brochure on cleaning up after painting and the disposal of paint, ring 1800-807-568 (free call). Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

Guarantee/Warranty

Recommendations for the use of this product are based on tests carried out at approved laboratories that are believed reliable. Both manufacturer and seller are not responsible for the results where the product is used under conditions beyond our/their control. Under no circumstances will the manufacturer or Cease-Fire or its agents or servants, be liable for consequential damages or damages to anyone in excess of the purchase price of the product or services.

Distributed by Cease Fire Technologies Ltd

Unit 1 / 16 Jarrah Street Cooroy 4563 Queensland Australia

Fax: 07 5452 5658

E-Mail: info@ceasefire.com.au