

**SAFETY DATASHEET****FireMortar-360***Issue Date: 30/8/2019**Review Date: 30/8/2024*

**NAME** BOSS Passive Fire  
**ADDRESS** Unit 1, 16 Atkinson Rd, Taren Point NSW 2229 AUSTRALIA  
**PHONE** 1300 502 677  
**FAX** 1300 602 677  
**EMAIL** info@bossfire.com.au  
**WEB** bossfire.com

**1. SUBSTANCE IDENTIFICATION**

<b>Product Name</b>	FireMortar-360
<b>Product Code</b>	FM360
<b>Use/Description</b>	Synthetic mortar which, when mixed with water, produces a trowel able or pourable compound suitable for sealing holes in walls and floors, which prevents the passage of fire and smoke.

**2. COMPOSITION**

<b>Contains</b>	Controlled blend of accelerated calcium sulphate, calcium hydroxide, expanded perlite aggregate and limestone flour with organic additives.
-----------------	---

<b>Name</b>	<b>Amount</b>	<b>CAS No</b>	<b>EINECS</b>
Calcium Sulphate	>80%	10034-76-1	231-900-3
Limestone	<21%	471-31-1	215-279-6

Impurities: Contains &lt;1% Organic Substances

**3. HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Repairable dust inhaled over a prolonged period of time could constitute a health hazard. This product releases alkali in contact with water, which could be irritating to skin and eyes.
---------------------	---

#### 4. FIRST AID MEASURES (SYMPTOMS)

<b>Skin Contact</b>	May cause irritation
<b>Eye Contact</b>	May cause irritation
<b>Ingestion</b>	May feel ill and tightness in the throat
<b>Inhalation</b>	May cause irritation to the throat and nose

#### 5. FIRST AID MEASURES (ACTION)

<b>Skin Contact</b>	Wash thoroughly with plenty of soap and water
<b>Eye Contact</b>	Bathe with water for 15 minutes, seek medical advice
<b>Ingestion</b>	Remove to fresh air, give water to drink. Do not induce vomiting. Seek medical attention immediately.
<b>Inhalation</b>	Remove to fresh air, give water to drink. If symptoms persist seek medical advice.

#### 6. FIRE FIGHTING MEASURES

<b>Suitable Extinguishers</b>	All standard fire-fighting media
<b>Protective Equipment</b>	Addition of water will produce alkaline by-products, suitable protective clothing should be worn to prevent contact

#### 7. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Refer to Section 9 of this SDS for personal protection details
<b>Environmental Precautions</b>	Do not discharge into drains or rivers Dispose of in accordance with local authority requirements
<b>Clean-up Procedures</b>	Vacuum system. Utilise water spraying to prevent airborne dust. Avoid dry sweeping which creates dust. Dispose of in accordance with local/national authority requirements.

## 8. HANDLING & STORAGE

<b>Handling Requirements</b>	The product should be handled to minimize the creating of airborne dust particles. Protective glasses, dust masks, long trousers and protective sleeving should be worn. Barrier cream is recommended on naked skin surfaces. Wet clothing will yield alkaline residue. Assess manual handling requirements.
<b>Storage Conditions</b>	Store in a cool dry, well ventilated area off the ground and palletized
<b>Suitable Packaging</b>	Store in original packaging, tightly sealed

## 9. EXPOSURE CONTROL & PERSONAL PROTECTION

<b>Exposure Control</b>	LTTEL: Inhalable dust 10mg.m3 / Respirable 4mg.m3 (8 hour TWA reference period)
<b>Respiratory Control</b>	Ensure adequate ventilation for airborne dust particles Use of suitable dust mask is recommended
<b>Hand Protection</b>	Protective gloves
<b>Eye Protection</b>	Protective glasses
<b>Skin Protection</b>	Full length trousers, long sleeved tee shirt and impervious boots

## 10. PHYSICAL & CHEMICAL PROPERTIES

<b>State</b>	Free flowing powder
<b>Colour</b>	Off white
<b>Odour</b>	Alkaline
<b>Solubility in Water</b>	Fully miscible in water
<b>Relative Density</b>	1.0 – 1.1
<b>pH</b>	Alkaline in water

## 11. STABILITY & REACTIVITY

<b>Stability</b>	Stable under normal conditions
<b>Conditions to Avoid</b>	Water / moisture (not controlled)
<b>Materials to Avoid</b>	None known
<b>Haz. Decomp. Products</b>	The addition of water produces alkali by-products

## 12. TOXICOLOGICAL INFORMATION

<b>Acute Toxicity</b>	No evidence of acute toxicity
<b>Skin Corrosion / Irritation</b>	Not classified
<b>Serious Eye Damage / Irritation</b>	May cause mechanical irritation
<b>Respiratory</b>	No evidence
<b>Germ Cell Mutagenicity</b>	No evidence
<b>Carcinogenicity</b>	No classification
<b>Reproduce Toxicity</b>	No evidence
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met

## 13. ECOLOGICAL INFORMATION

<b>Ecotoxicity Values</b>	Not established
<b>Persistence and Degradability</b>	Not established
<b>Bioaccumulative Potential</b>	Not established
<b>Mobility</b>	Not established
<b>PBT Identification</b>	Not established
<b>Other Adverse Effects</b>	No specific adverse effects known

## 14. DISPOSAL CONSIDERATIONS

<b>Disposal Operations</b>	No special disposal necessary, avoid production of dust Dispose of in accordance with local authority requirements Do not discharge into drains or sewage systems
<b>Disposal of Packaging</b>	Dispose of as normal industrial waste according to local or national legislation

## 15. TRANSPORT HAZARDS

<b>Transport Hazards</b>	No regulations apply for the transport of this material Not classified as hazardous road, rail, sea or air transport
<b>Hazard Symptoms</b>	None. Respirable dust from any fine powder could, if inhaled over a prolonged period of time, constitute a health hazard.

## 16. ADDITIONAL INFORMATION

<b>Disclaimer</b>	<p>The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication.</p> <p>The information given is designed only as a guidance for safe handling, use, processing, storage transportation, disposal and release and is not considered a warranty or quality specification.</p> <p>The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.</p>
-------------------	---

### LIMITATION

BOSS Passive Fire Pty Ltd has provided the above technical information in good faith and to the best of its knowledge. This information was deemed to be correct at the time of publication. Should any data come to BOSS Passive Fire's attention relating to the fire resistance or performance of the product described BOSS Passive Fire reserve the right to amend this report.

BOSS Passive Fire strive to constantly improve and develop products so this information may change without notice.

The information contained herein has been developed as a guide only and it does not constitute a guarantee of compliance of all applications. Each project and/or application may have specific requirements and you should investigate these carefully. Ensure that you have read and understood the appropriate certification relative to your needs, and ensure you seek acceptance from the Certifying Authority or compliance inspector before installation. For updates on the range of BOSS Fire® certification please contact BOSS Technical Services on +61 2 9531 8591.

### FURTHER INFORMATION

For additional technical information on the performance of BOSS FireMortar-360™, other BOSS Fire® products or any other BOSS Fire® related information please contact us on:

**AU:**  
1300 50 2677  
Bossfire.com.au

**NZ:**  
0800 50 2677  
Bossfire.co.nz

**Admin:**  
+612 9531 8591  
info@bossfire.com.au  
Unit 1, 16 Atkinson Rd Taren Point NSW 2229 AUSTRALIA